



ANHO er en helantistatisk rengjøringslange i polyetylen for støvsuging der det er risiko for støveksplasjon. En lett og fleksibel, overkjørbar slange med relativt glatt innside og gode kjemiske egenskaper.

Leveres i lengder på 7,5 eller 15 m.
Ø38 og Ø50 finnes også i 10, 20 og 30 m lengder.

Elektrisk ledende EVA. Motstand: $\leq 10^6$ Ohm/cm.

Temperaturområde: -50 til +60 °C.

Farge: svart.

Art.nr	Ø innv.	Ø utv.	L	Vekt pr mtr (kg)
ANHO-032	32.5	42	7.5/15	0.3
ANHO-038	38.5	48	7.5/10/15/20/30	0.34
ANHO-045	45.5	55	7.5/15	0.47
ANHO-050	51	60.5	7.5/10/15/20/30	0.54
ANHO-063	63.5	74	7.5/15	0.74
ANHO-076	76.5	87.5	7.5/15	0.87



Conductive POLYETHYLENE (PE) and ELASTOMER spiral hose, with reinforcement on the external spiral with antiabrasive function, for extraction of air and dust, where absence of electrostatic accumulation is required.



Smooth surfaces



Flexibility



Abrasion
Resistance



Temperature
range

-20 °C +60 °C
-4 °F +140 °F



Crushing
resistance



Conductive

According to CEI EN 61340-2-3, concentric electrodes method; surface resistance $\leq 10^4$ Ohm (tested after 24h)



Electrical
resistance

According to
ISO 8031: $\leq 100k\Omega$



Chemical
resistance

LLDPE Table